			526 Re	ec'd PCT/PTO Z9 JAN 2001					
ORM P	TO-139 -95)	0 (Modified) U.S. DEPARTMENT	OR COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER					
	TR	RANSMITTAL LETTER	TO THE UNITED STATES	98M035					
		DESIGNATED/ELECTE	ED OFFICE (DO/EO/US)	U.S. APPLICATION NO. (IF KNOWN SEE 37 CFR					
		CONCERNING A FILIN	G UNDER 35 U.S.C. 371	9//1440//					
	I	IONAL APPLICATION NO. PCT/GB99/02480	INTERNATIONAL FILING DATE 28 July 1999	PRIORITY DATE CLAIMED 29 July 1998					
		NVENTION for Manufacture of Molecula	nr Sieves						
		r(s) for do/eo/us	MEDTENC M. HALL M. MODELER	NUMBER OF THE VANIGORNA AND A STATE OF THE VALUE					
		IOT, Cornelius, W.; VAUGH		R, Wilfried, J.; JANSSEN, Marcel, J.; VAN					
			tes Designated/Elected Office (DO/EO/US) t	he following items and other information:					
••			- '	-					
1.			tems concerning a filing under 35 U.S.C. 371 UENT submission of items concerning a fili						
2.		-	in national examination procedures (35 U.S.)	·					
э.		examination until the expiration	of the applicable time limit set in 35 U.S.C.	371(b) and PCT Articles 22 and 39(1)					
4.		A proper Demand for Internation	al Preliminary Examination was made by the	e 19th month from the earliest claimed priority date.					
5.	\boxtimes	A copy of the International Appl	ication as filed (35 U.S.C. 371 (c) (2))						
		 a.							
£13									
40		c. \square is not required, as the application was filed in the United States Receiving Office (RO/US).							
C Contract		A translation of the International Application into English (35 U.S.C. 371(c)(2)).							
alle	\boxtimes	A copy of the International Search	ch Report (PCT/ISA/210).						
8	\boxtimes	Amendments to the claims of the	International Application under PCT Article	e 19 (35 U.S.C. 371 (c)(3))					
100		a. are transmitted herewith	n (required only if not transmitted by the Inte	ernational Bureau).					
A.d		b. 🗆 have been transmitted b	y the International Bureau.						
2		c. 🔲 have not been made; he	wever, the time limit for making such amen	dments has NOT expired.					
200		d. Make not been made and	d will not be made.						
9.		A translation of the amendments	to the claims under PCT Article 19 (35 U.S.	.C. 371(c)(3)).					
10.		An oath or declaration of the inv	entor(s) (35 U.S.C. 371 (c)(4)).						
f#	\boxtimes	A copy of the International Preli	minary Examination Report (PCT/IPEA/409).					
2		A translation of the annexes to the (35 U.S.C. 371 (c)(5)).	ne International Preliminary Examination Re	port under PCT Article 36					
It	ems 1	3 to 18 below concern documen	t(s) or information included:						
13.	M	An Information Disclosure State	ement under 37 CFR 1.97 and 1.98.						
14.		An assignment document for rec	ording. A separate cover sheet in compliance	e with 37 CFR 3.28 and 3.31 is included.					
15.	\boxtimes	A FIRST preliminary amendme	nt.						
		A SECOND or SUBSEQUENT	preliminary amendment.						
16.	\boxtimes	A substitute specification.							
17.		A change of power of attorney a	nd/or address letter.						
18.	\boxtimes	Certificate of Mailing by Expres							
19.		Other items or information:							

JC97	Rec'd	PCT/PT	ГО	2	9	JAN	200:	
								_

U.S. A	J.S. APPLICATION NO (IF KNOWN, SEE 37 CFR INTERNATIONAL APPLICATION NO PCT/GB99/02480						ATTORNEY'S DOCKET NUMBER 98M035			
20.		lowing fees are submi					CA	LCULATION	S PTO USE ONLY	
BASIC		L FEE (37 CFR 1.4)		(5)): or JPO		PO 40 00	Г			
				d to USPTO (37 CFR 1.482)		\$840.00	1			
	No internation	onal preliminary exam	ination fee	paid to USPTO (37 CFR 1.482 37 CFR 1.445(a)(2))	2)	70.00				
2	Neither inter	national preliminary	vaminatio	fee (37 CFR 1 482) por		\$760.00				
	International International	search fee (37 CFR 1 preliminary examina	.445(a)(2) tion fee pai	paid to USPTO	:	\$970.00				
	anu an ciain			ticle 33(2)-(4)		\$96.00	L.			
				ATE BASIC FEE AM				\$1,000.00		
months	s from the ear	0 for furnishing the o liest claumed priority	ath or decla date (37 C	ration later than 2 FR 1.492 (e)).	20	⊠ 30		\$130.00		
CL	AIMS	NUMBER FI	LED	NUMBER EXTRA		RATE				
Total c			- 20 =	4	x	\$18.00		\$72.00		
_	ndent claims		- 3 =	0	x	\$78.00	<u> </u>	\$0.00		
Multip	ole Dependen	Claims (check if app		inorm all are	<u> </u>			\$0.00		
Daduat	ion of 1/2 for			ABOVE CALCULAT			_	\$1,202.00		
must al	lso be filed (I	Note 37 CFR 1.9, 1.27	7, 11 applica 7, 1.28) (ch	ble. Verified Small Entity Sta eck if applicable).	temen	· -		\$0.00		
112				SUB	TOT	AL =		\$1,202.00		
Process months	sing fee of \$1 from the ear	30.00 for furnishing to liest claimed priority	he English date (37 C	translation later than 2 FR 1.492 (f)).	20	□ 30 +		\$0.00		
253				TOTAL NATIONAL	L FE	E =		\$1,202.00		
Fee for accomp	recording the panied by an a	enclosed assignment appropriate cover shee	(37 CFR 1 t (37 CFR	.21(h)). The assignment must 3.28, 3.31) (check if applicab	be le).			\$0.00		
10				TOTAL FEES ENCL	OSI	ED =		\$1,202.00		
13							Amor	unt to be: efunded	\$	
647								charged	S	
	Please charg	he amount of ge my Deposit Accour		to cover the above fees is end 05-1712 in the amount of			to	cover the abov	re fees	
	A duplicate	copy of this sheet is	enclosed.							
×	The Commi	ssioner is hereby auth	orized to el	narge any fees which may be re	avirad	on anadit				
	to Deposit A			A duplicate copy of this sheet is			ny ove	граутисть		
NOTE:	: Where an :	appropriate time lim	it under 3'	CFR 1.494 or 1.495 has not let the application to pending s	haan r	nat a natiti	on to i	revive (37 CFF	₹	
				e the application to pending a	natus.					
SEND.	ALL CORRE	SPONDENCE TO:			-	> J	1+	- 1,		
Edwar	rd F. Sherer				SIG	NATURE	١١١	· Men	A	
		ical Company								
P. O. 1	Box 2149				-	ward F. Sh	ierer			
Bayto	wn, TX 7752	22-2149			NA.	ME				
					29,	588				
	REGISTRA					GISTRATIC	N NU	MBER		
	Januar					uary 29, 2	001			
	_					ΓE				

JC97 Rec'd PCT/PTO 2 9 JAN 200#

"PATENT"

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

§

§

§

§

§

§

§

§ §

§

§

In re Application of VERDUIJN, Johannes Petrus (deceased) MERTENS, Machteld M. MORTIER, Wilfried J. JANSSEN, Marcel J. G. VAN OORSCHOT, Cornelius W. VAUGHAN, David E. PROCESSES FOR MANUFACTURE OF MOLECULAR SIEVES PCT/GB99/02480

Baytown, Texas January 29, 2001

PCT International Services

Division

Box PCT Commissioner of Patents and Trademarks Washington, D.C. 20231

Docket No. 98M035

Int'l Filing Date: 28 July 1999 Priority Date Claimed: 29 July 1998

PRELIMINARY AMENDMENT UNDER 37 CFR 1.121

Sir

Attached please find our PCT application, ready for examination before the United States Patent and Trademark Office.

Enclosed are the following documents:

- (1) copy of the International Application as filed:
- (2) substitute specification:
- (3) International Search Report and cited references;
- (4) IPER.

PRELIM DOT

Please examine the substitute specification rather than the originally filed application. No new matter has been added to the substitute specification.

The amended claims are being submitted to correct multiple dependent claims for better U.S. practice and examination and also to reduce fees.

In view of the foregoing, it is respectfully submitted that all claims of the application are in condition for allowance and favorable action thereon is respectfully requested.

Respectfully submitted.


January 29, 2001

Date

Edward F. Sherer Attorney for Applicant Registration No. 29,588

ExxonMobil Chemical Company Law Technology P. O. Box 2149 Baytown, Texas 77522-2149 281-834-5933

SUBSTITUTE SPECIFICATION



2007 NOVE PULLPIO 2 9 JAN 2001

PROCESSES FOR MANUFACTURE OF MOLECULAR SIEVES

This invention relates to molecular sieves and processes for their

manufacture. More especially it relates to processes in which synthesis mixtures are seeded to control process conditions and product characteristics. The invention relates primarily to the manufacture of phosphorus-containing molecular sieves.

It is well-known that seeding a molecular sieve synthesis mixture

10 frequently has beneficial effects, for example in controlling the particle size of the
product, avoiding the need for an organic template, accelerating synthesis, and
improving the proportion of product that is of the intended structure type.

In U.S. Patent No. 4 440 871, the preparation of a number of phosphoruscontaining molecular sieves is described, and it is stated that the crystallization
procedure may be facilitated by stirring, or other moderate agitation of the
synthesis mixture, or by seeding it with crystals of the molecular sieve to be
produced or one of a topologically similar structure.

The patent particularly describes processes for the manufacture of numerous crystalline microporous silicoaluminophosphates (SAPO's) including SAPO-34, employing sources of silicon (e.g., a silica sol), aluminium (e.g., hydrated aluminium oxide), and phosphorus (e.g., orthophosphoric acid), and an organic template, for example tetraethylammonium hydroxide (TEAOH), isopropylamine (iPrNH₂) or di-n-propylamine (DPA). The patent, the disclosure of which is incorporated by reference herein, gives X-ray diffraction data for the SAPO's and describes their utilities in catalysis and absorption.

It has now been found that advantages result from the use of colloidal seeds in the manufacture of phosphorus-containing molecular sieves.

The present invention accordingly provides in a first aspect a process for the manufacture of a crystalline molecular sieve containing phosphorus in its framework, which process comprises treating a synthesis mixture comprising

elements necessary to form the phosphorus-containing molecular sieve and colloidal crystalline molecular sieve seeds for a time and at a temperature appropriate to form the desired molecular sieve.

It has surprisingly also been found that the seed crystals may be of a 5 structure type different from that of the desired molecular sieve. Such seeding may be regarded as "heterostructural", whereas seeding with seeds of the same structure type is termed "isostructural", whether or not the seeds are of the same composition (i.e., contain the same elements in the same proportions) as the crystalline molecular sieve to be produced.

Where the seeds are of a structure type different from those of the desired molecular sieve, advantageously the seeds and the desired molecular sieves are topologically similar, for example are members of the ABC-6 group of materials, as described in "Topochemistry of Zeolites and Related Materials", J.V. Smith, Chem. Rev. 1988, 88, 149 at 167, the disclosure of which review article is 15 incorporated herein by reference. The ABC-6 group includes, inter alia, the Offretite, Chabazite and Levyne structures.

As used in this specification, the term "structure type" is used in the sense described in the Structure Type Atlas, Zeolites 17, 1996.

The present invention accordingly provides in a second aspect a process 20 for the manufacture of a crystalline molecular sieve containing phosphorus in its framework, which comprises treating a synthesis mixture comprising elements necessary to form a phosphorus-containing molecular sieve of a first structure type and colloidal molecular sieve seed crystals of a second, different, structure type, for a time sufficient and at a temperature appropriate to form the molecular 25 sieve of the first structure type.

In further aspects, the invention provides the use, in the synthesis of a phosphorus-containing crystalline molecular sieve, of colloidal seed crystals to control the particle size of the product, or to accelerate the formation of the

1.0

product, or both to control the particle size and accelerate the formation of the product.

As the phosphorus-containing molecular sieves to be prepared by the processes of the invention, there may be mentioned more especially

aluminophosphates and silicoaluminophosphates. As examples of structure types produced there may be mentioned more especially molecular sieves of the structure types CHA and LEV. As seeds, there may for example be used crystals of structure type LEV, OFF, and CHA. As specific materials to be used, there may be mentioned Levyne, ZSM-45, Chabasite, Offretite and SAPO-34.

The seeds used in the present invention may be obtained by methods described herein or known in the art or described in the literature.

Manufacture of OFF-structure type seed crystals, in particular colloidal

Offretite seeds, may be carried out as described in International Application No.

WO 97/03020, while suitable procedures, including details of synthesis mixtures
and hydrothermal treatment, for the manufacture of LEV- and CHA- structure
type crystals are described in EP-A-91048, 91049, 107 370, 143 642 and U.S.
Patent No. 4 495 303 (for LEV) and GB-A-868 846 and 2 061 500 and U.S.
Patents Nos. 3 030 181 and 4 544 538 (for CHA), the disclosures of all of which
are incorporated by reference herein. Manufacture of CHA- and LEV-structure
type seed crystals is advantageously carried out as described in the examples
below.

Apart from the presence of the seeds, the synthesis mixture used in the present invention is typically one that is known in the art or as described in the literature as suitable for the production of the molecular sieve concerned. This is also the case for the conditions of treatment, except that the presence of the seeds may make possible the reduction of reaction times or may obviate stirring if that were otherwise necessary.

In general, the treatment of the synthesis mixture to yield the desired phosphorus-containing crystalline molecular sieve, usually termed hydrothermal

treatment, though strictly that term should be used only for treatments in which there is vapour-phase water present, is advantageously carried out under autogenous pressure, for example in an autoclave, for example a stainless steel autoclave which may, if desired, be ptfe-lined. The treatment may, for example, 5 be carried out at a temperature within the range of from 50, advantageously from 90, especially 120, to 250°C, depending on the molecular sieve being made. The treatment may, for example, be carried out for a period within the range of from 20 to 200 hours, preferably up to 100 hours, again depending on the molecular sieve being formed. The procedure may include an ageing period, either at room 10 temperature or, preferably, at a moderately elevated temperature, before the hydrothermal treatment at more elevated temperature. The latter may include a period of gradual or stepwise variation in temperature.

For certain applications, the treatment is carried out with stirring or with rotating the vessel about a horizontal axis (tumbling). For other applications, 15 static hydrothermal treatment is preferred. If desired, the synthesis mixture may be stirred or tumbled during an initial part of the heating stage, for example, from room temperature to an elevated, e.g., the final treatment, temperature, and be static for the remainder. Agitation generally produces a product with a smaller particle size and a narrower particle size distribution than static hydrothermal treatment.

The seeds are generally present in the synthesis mixture in a concentration of up to 10000, advantageously at most 3000, more advantageously at most 1500, and preferably at most 1000, more preferably at most 500, and most preferably at most 350 ppm, based on the total weight of the synthesis mixture. A minimum 25 seeding level is generally 1 ppb (0.001 ppm), advantageously at least 0.1, more advantageously at least 1, and preferably at least 10, ppm, based on the total weight of the synthesis mixture. Advantageous ranges of proportions are from 1 to 2000, preferably 100 to 1500, and most preferably 100 to 250, ppm.

The colloidal seeds are advantageously incorporated in the synthesis mixture in the form of a suspension, advantageously in an aqueous medium, preferably water, or another liquid component of the synthesis mixture. Less preferably they may be added in dry, but not calcined, form. It is believed that calcination significantly reduces the activity of small crystallites to act as seeds; similarly any other treatment that reduces the seeding activity of materials should be avoided. As used herein, the term "colloidal", when used of a suspension, refers to one containing discrete finely divided particles dispersed in a continuous liquid phase and preferably refers to a suspension that is stable, in the sense that no visible separation occurs or sediment forms, in a period sufficient for the use intended, advantageously for at least 10, more advantageously at least 20, preferably at least 100, and more preferably at least 500, hours at ambient temperature (23°C).

The maximum size of the particles for the suspension to remain stable

(peptized) will depend to some extent on their shape, on the nature and pH of the
continuous medium, as well as on the period during which the suspension must
remain usable. In general, the maximum dimension will be 1µm, advantageously
500, more advantageously 400, preferably 300, more preferably 200, and most
preferably 100, nm. The particles may be of spherical, columnar, rod, coffin,

platelet, or needle shapes. Where particles are platelets or needles, the dimension
referred to is their smallest dimension.

The minimum dimension is such that the particles do not dissolve or redissolve in the medium, and for crystallinity they must contain at least a small plurality, advantageously at least two, preferably four, unit cells of the crystal.

The minimum particle size is in general 5, advantageously 10, and preferably 20, nm. Mean particle sizes are generally in the range 5 to 1000, advantageously 10 to 300, more advantageously 10 to 200, and preferably 20 to 100, nm.

Advantageously at least 50%, more advantageously at least 80%, and more preferably at least 95%, by number, of the particles are greater than the given

minima, smaller than the given maxima, or within the given ranges of particle size. Measurements of particle size may be effected by electron microscopy, for example using a Philips SEM 515 unit.

If the product is desired in small particle size form, a larger number of

smaller sized seeds is desirably employed. The smaller the particle size of the
seeds, the lower the weight percentage that is effective. The crystals are
advantageously stirred into the synthesis mixture for a time sufficient to provide a
uniform dispersion, this time being dependent primarily on the viscosity of the
synthesis mixture, and also on the scale and type of the equipment, but ranging

generally from 30 seconds to 10 minutes.

More especially, the invention provides processes and uses in which colloidal LEV structure type seeds are used in the manufacture of a phosphoruscontaining crystalline molecular sieve.

A colloidal suspension of LEV may be obtained by synthesizing a LEV

structure type molecular sieve by hydrothermal treatment of an appropriate
synthesis mixture, and separating the product from the synthesis mixture, washing
the product, and recovering the resulting wash liquid.

Examples of the LEV structure type include Levyne, NU-3, ZK-20, ZSM-45 and SAPO-35.

The colloidal LEV seeds are especially suitable to provide crystalline molecular sieves of the CHA structure type. Examples of such CHA materials are SAPO-, AlPO-, MeAPO-, MeAPSO-, ElAPSO- and ElAPO –47 and especially the corresponding –34 materials. In these formulae, El represents magnesium, zinc, iron, cobalt, nickel, manganese, chromium or mixtures of any two or more such elements. CHA structure type seeds may also be used in synthesis of these materials. LEV and CHA structure type seeds may be used in the synthesis of SAPO-, AlPO-, MeAPO-, MeAPSO-, ElAPSO- and ElAPO- materials of the LEV structure type, e.g., the –35 materials. Where a material is referred to as, for example, a SAPO material, this terminology includes the possibility that

additional elements may be present, either in the framework or otherwise, as in the case discussed below, of Ni-SAPO.

Among these materials, SAPO-34 has been found to have considerable utility in catalysing the conversion of methanol to light olefins, primarily those

with 2 to 4 carbon atoms (see, for example, U.S. Patent No. 5 126 308, also incorporated by reference herein). It would be of value to be able to increase the proportion of ethylene in the product.

The present invention accordingly also provides a process for the manufacture of SAPO-34 in which the percentage area contribution of Broensted acid sites to the total OH area in the IR spectrum is at least 30%, advantageously at least 50%, and preferably at least 60%, by a procedure in which the synthesis mixture contains colloidal crystalline molecular sieve crystals. In certain embodiments, percentage area contribution is at most 95%.

More especially, the invention further provides a process for the

manufacture of SAPO-34, which comprises treating a synthesis mixture having a
molar composition appropriate for SAPO-34 formation and also containing
colloidal OFF-type, CHA-type, or LEV-type seed crystals, advantageously of
mean particle size of at most 400 nm, for a time and at a temperature sufficient to
form SAPO-34.

The process of the invention is capable of providing SAPO-34 in which the particle size is at most 0.75 μm, advantageously at most 0.5 μm. Advantageously the particle size distribution is such that 80 % (by number) of the particles are within ±10 % of the mean.

In a further aspect, the invention provides a process for the conversion of an oxygenate, especially methanol, to olefins which comprises contacting the oxygenate with a catalyst under conversion conditions, the catalyst comprising SAPO-34 produced in accordance with the invention.

The olefins produced are advantageously light olefins, by which is to be understood an olefin mixture of which at least 50% by weight contain from 2 to 4 carbon atoms.

Referring now more especially to the Broensted acid site aspect of the

invention, it is believed (without the invention being limited by any theoretical
considerations) that the Broensted acidity is important in the catalytic activity,
especially in oxygenate to olefin conversion, of a molecular sieve, and that a
molecular sieve in which the bridged hydroxyl groups represent a high proportion
of the hydroxyl groups in the crystal will have a high activity. Infra-red analysis
of a highly active product of the invention (described as are the methods of
measurement in more detail in the Examples below) shows that in the SAPO-34
OH region, 4000 to 3000 cm⁻¹, two peaks, at ~3620 and ~3595 cm⁻¹, are the main
features, while less active samples show a number of bands in the range from 3750
to 3620 cm⁻¹, which are assigned to Al-OH, Si-OH, and P-OH groups on an

A further IR spectrum characteristic associated with catalytic activity is a high peak intensity in the T-O asymmetric stretch region, at 1050 to 1150 cm⁻¹, intensity being indicated by both height and sharpness, i.e., a high level of internal crystallinity. It is accordingly believed that a correlation exists between high 20 internal crystallinity, or crystal perfection, and a high contribution of Broensted OH groups to the total OH content of the material.

Further, in common with many other molecular sieves, the catalytic activity and stability of activity of SAPO-34 are in general terms greater the smaller the particle size.

The synthesis mixture for producing SAPO-34 according to the invention advantageously has a molar composition, apart from the colloidal seeds, within the following ranges:

P₂O₅ : Al₂O₃ 0.9 to 1.2 : 1

SiO₂ : Al₂O₃ 0.05 to 0.4 : 1

H₂O : Al₂O₃ 10 to 100 : 1

together with an organic template, advantageously tetraethylammonium hydroxide

(TEAOH), dipropylamine (DPA), isopropylamine or morpholine, or a mixture of
two or more such templates, in a proportion appropriate to yield SAPO-34. A
preferred template mixture comprises TEAOH and DPA.

In a particularly advantageous embodiment of the invention the synthesis mixture advantageously contains a source of metallic elements, especially a Group VIII metal, more especially nickel. A convenient source of the metal is a water-soluble salt, for example the nitrate. The metal is advantageously present in a molar proportion calculated as oxide relative to Al₂O₃ within the range of 0.001 to 0.05, preferably 0.005 to 0.01. The presence of nickel enhances the catalytic activity at least in oxygenate conversion. Other suitable Group VIII metals include Fe and Co, while other suitable metals include Mn, Cr, Cu, Zn, Mg, Ti and Zr.

The sources of the materials may be any of those in commercial use or described in the literature, as may the preparation of the synthesis mixture.

The invention also provides the products of the processes and of the uses

of the earlier aspects of the invention. The products, if required after cation
exchange and/or calcining, have utility as catalyst precursors, catalysts, and
separation and absorption media. They are especially useful in numerous
hydrocarbon conversions, separations and absorptions. They may be used alone,
or in admixture with other molecular sieves, in particulate form, supported or

unsupported, or in the form of a supported layer, for example in the form of a
membrane, for example as described in International Application WO 94/25151.

Hydrocarbon conversions include, for example, cracking, reforming, hydrofining,
aromatization, oligomerisation, isomerization, dewaxing, and hydrocarbons,
naphtha to light olefins, higher to lower molecular weight hydrocarbons,

alkylation, transalkylation, disproportionation or isomerization of aromatics).

Other conversions include the reaction of alcohols with olefins and the conversion of oxygenates to hydrocarbons.

Conversion of oxygenates may be carried out with the oxygenate, e.g.,

methanol, in the liquid or, preferably, the vapour phase, in batch or, preferably,
continuous mode. When carried out in continuous mode, a weight hourly space
velocity (WHSV) based on oxygenate, of advantageously 1 to 1000, preferably 1
to 100, hour may conveniently be used. An elevated temperature is generally
required to obtain economic conversion rates, e.g., one between 300 and 600°C,
preferably from 400 to 500°C, and more preferably about 450°C. The catalyst
may be in a fixed bed, or a dynamic, e.g., fluidized or moving, bed.

The oxygenate feedstock may be mixed with a diluent, inert under the reaction conditions, e.g., argon, nitrogen, carbon dioxide, hydrogen, or steam.

The concentration of methanol in the feedstream may vary widely, e.g., from 5 to 90 mole per cent of the feedstock. The pressure may vary within a wide range, e.g., from atmospheric to 500 kPa.

The following Examples, in which parts are by weight unless otherwise indicated, illustrate the invention. The source and purity of starting materials are those first given, unless indicated otherwise.

Example 1

2.0

This example illustrates the manufacture of a LEV-type zeolite of particle size suitable for use as seeds in the manufacture, inter alia, of phosphoruscontaining crystalline molecular sieves.

In a first stage, 15.95 parts of sodium aluminate (Dynamit Nobel, 53 % Al₂O₃, 41 % Na₂O, 6 % H₂O), 19.95 parts of sodium hydroxide (Baker, 98.6 %) and 5.58 parts of potassium hydroxide (Baker, 87.4 %) were dissolved in 151.06 parts of water, and heated to boiling until a clear solution was obtained. After

cooling to room temperature, water loss was compensated, to form Solution A. 270.60 parts of colloidal silica (Ludox HS40, 40 % SiO₂) were mixed with 106.12 parts of choline chloride (R. Fluka) forming a viscous mass, and Solution A added with stirring at increasing speed as the viscosity decreased, together with 190 parts 5 of rinse water, mixing then continuing for a further 5 minutes. The molar composition was:

1.95 Na₂O:0.24 K₂O:0.46 Al₂O₃:10 SiO₂:4.187 R:155 H₂O.

To 290 parts of this mixture, 0.49 parts of conventional LEV zeolite seeds were added, and a sample transferred to an autoclave, where it was heated in a 120°C oven for 144 hours. The product was washed, recovered by centrifuging and dried overnight at 120°C. The product comprised spherical aggregates of from 2 to 2.5 µm, made up of ~100 nm particles, with an X-ray diffraction pattern 15 (XRD) of ZSM-45, a zeolite of LEV-type structure, as described in EP-A-107 370 (Mobil).

The product was used as seeds in the next stage, in which 8.38 parts of sodium aluminate, 10.53 parts of sodium hydroxide, 2.96 parts of potassium hydroxide, and 78.95 parts of water were treated as described above to form a 20 Solution A. Solution A was then added to a mixture of 142.42 parts of colloidal silica and 55.5 parts of choline chloride, together with 100.00 parts of rinse water and mixed as described above, with the addition of 0.68 parts of the first stage seeds. The reaction mixture was heated in an autoclave at 120°C for 174 hours, the product recovered by washing, centrifuging and drying having an XRD similar 25 to that of the first stage. The second supernatant of the washing procedure was not clear, and had a pH of 10.3. It was found to be a dispersion with a solids content of 2.3 %. Analysis by scanning electron microscopy (SEM) and XRD showed ~100 nm unaggregated crystals with a ZSM-45 structure, LEV structure type.

Example 2

This example illustrates the manufacture of a chabasite dispersion suitable for use, in turn, for seeding in

5 SAPO-34 manufacture. The seeds were prepared as follows:

A synthesis mixture was prepared as described in the first part of Example 1, except that as seeds the colloidal sol from the second supernatant of the second part of Example 1 was used, at a seeding level of 0.15% by weight of solids. The seeded synthesis mixture was heated in a stainless steel autoclave for 96 hours at 120°C, with a heat-up time of 3 hours. The product, recovered by centrifuging and drying, had an XRD pattern corresponding to ZSM-45. The first supernatant was not clear and yielded, after centrifuging at 11000 rpm and further washing, a dispersion with solids content 4.6%, of crystals of size about 100 nm, XRD showing the product to be ZSM-45. a LEV structure-type zeolite.

Solution A was prepared as described in Example 1 using the following components, in the proportions shown:

	NaOH	61.66
	КОН	28.73
20	Al(OH) ₃ (Alcoa, 99.3 %)	15.73
	H ₂ O	190.30

300.23 parts of colloidal silica and 168.89 parts of water were poured into a mixer, and Solution A added together with 12.65 parts of rinse water. After mixing for 5 minutes, 16 parts of the 4.6 % solids LEV slurry were added.

The molar composition of the synthesis mixture was:

 $3.8 \text{ Na}_2\text{O}:1.12 \text{ K}_2\text{O}:0.5 \text{ Al}_2\text{O}_3:10 \text{ SiO}_2:161 \text{ H}_2\text{O}$, with 927 ppm seeds.

The synthesis mixture was heated in an autoclave to 100°C over 2 hours, and maintained at that temperature for 96 hours. After cooling, the content of the autoclave, a milky suspension, was washed five times with demineralized water and centrifuged at 9000 rpm. After taking a sample for XRD and SEM, the remainder was redispersed to form a colloidal solution, stable over several days, with a solids content of 6.4 %. The XRD of the product shows it to be chabasite, with a uniform particle size 100 x 400 nm.

Example 3

15

5

This example illustrates the manufacture of SAPO-34 of small particle size and uniform size distribution.

A synthesis mixture was prepared from the following components in the proportions shown.

20

	Solution A	Component Al ₂ O ₃ (Pural SB Condea 75%)	Proportion 68.18
		H_2O	100.02
5	В	H ₃ PO ₄ (Acros, 85%)	115.52
		H_2O ,	80.27
	С	Colloidal Silica (Ludox AS40) H ₂ O, rinse	22.73 10.20
10		- /	
	D	TEAOH (Eastern Chemical, 40%)	182.85
	E	DPA (Fluka)	80.23
15	F	Seeds, 4.6 Wt.% LEV	31.95

Slurry A was prepared in a mixer, and Solution B added, when a viscous solution resulted. After leaving the solution to rest for 2 minutes, 26.84 parts of rinse water were added. After mixing the paste for 6 minutes, C was added, and 20 mixed for 2 minutes before adding Solution D. Upon adding E with 70.72 parts of rinse water two phases were formed. After a further 3 minutes mixing a visually homogeneous solution resulted and after a further 10 minutes mixing the seeds F were added. The molar composition was:

25 Al2O3:P2O5:0.3 SiO2:TEAOH:1.6 DPA:56 H2O.

+ 1860 ppm by weight LEV seeds.

The seeded gel was heated for 60 hours at 175°C in a stainless steel autoclave. The solid product was recovered by centrifugation, washed 11 times with water to a conductivity of about $18~\mu s/cm$, and dried at $120^{\circ}C$. XRD and SEM showed a pure SAPO-34 product with crystals between 0.2 and 1.3 μm , with a few crystals between 2 and $3\mu m$. Chemical analysis indicated a product of molar composition:

5

In a similar manner a synthesis mixture was prepared from the following components in the proportions shown.

10

	Soluti	on Component		Proportion
15	A	Al ₂ O ₃ (Pural SB Condea 75 %)	6	8.06
13		H_2O		100.15
	В	H ₃ PO ₄ (Acros, 85 %)	115.74	
20		H ₂ O, including rinse	10	04.92
	С	Colloidal Silica (Ludox AS40)		22.50
25		H ₂ O, rinse		10.20
	D	TEAOH (Eastern Chemical, 40 %)	18	3.31
30		H ₂ O, rinse		43.17
	E	DPA (Fluka)	80.79	
35		H ₂ O, rinse		26.27

Slurry A was prepared in a mixer, and Solution B added, when a viscous mixture resulted. After mixing for 6 minutes, Solution C was added, and mixed

for 2 minutes before adding Solution D which was mixed in for 5 minutes. When E was added, two phases were formed. After a further 15 minutes mixing a visually homogeneous mixture resulted. The molar composition was:

The synthesis solution was divided, and to one sample a 6.4 % slurry of CHA zeolite, prepared as described in Example 2, was added to give a seeding level 410 ppm, the other sample remaining unseeded.

The unseeded sample was heated in a stainless steel autoclave at 175°C for 60 hours. The seeded sample was divided, one part being heated, without stirring, in a ptfe-lined autoclave for 60 hours at 175°C, and the other being heated with tumbling in a stainless steel autoclave for 60 hours at 175°C.

The samples were allowed to cool, and the product recovered by washing
and drying at 120°C. In all cases, a pure SAPO-34 product was obtained, with a
molar chemical constitution and crystal sizes as follows:

Unseeded:

Al₂O₃: 0.91 P₂O₅: 0.33 SiO₂, 1 to 10 μm

20 Seeded,

static:

Al₂O₃: 0.89 P₂O₅: 0.31 SiO₂, 0.2 to 1.5 μm

Seeded,

tumbled:

Al₂O₃: 0.91 P₂O₅: 0.35 SiO₂, ~0.5 μm.

25

10

The benefits of reduced crystal size and size distribution of seeding with colloidal chabasite seeds are apparent, especially when combined with tumbling.

Example 4

This example illustrates the use of colloidal Offretite seeds in the manufacture of SAPO-34. The colloidal Offretite was prepared as described in Example 2 of WO 97/03020. A synthesis mixture was prepared as described in Example 3, with the following molar composition:

Al₂O₃: P₂O₅: 0.3 SiO₂: TEAOH: 1.6 DPA: 51 H₂O.

To this was added a portion of a 5.36 % solids content colloidal offretite slurry (crystal size below 100 nm) to give a seeding level of 203 ppm.

Hydrothermal treatment and product recovery were carried out as described in Example 3. The product obtained was pure SAPO-34, the particle size of crystals being mainly between 0.2 and 1.3 μm, with a few crystals between 2 and 3 μm

15 present.

Comparative Example A

This example illustrates the use of powdered LEV, contaminated with

some Offretite, in SAPO-34 manufacture. To the same synthesis mixture

prepared for use in Example 4 were added a LEV powder in a proportion to give a

seed level of 217 ppm. The powder was mixed into the synthesis mixture gel by

shaking the gel in a polypropylene bottle for 2 minutes. Hydrothermal treatment

and product recovery were carried out as described in Example 4. The product

was pure SAPO-34, with the majority of the crystals of size between 0.5 and 2.5

µm. Comparison of this example with Example 4 shows that colloidal seeds at

approximately the same weight ratio yield smaller crystals.

Example 5

In this example, the effect of seeding on Ni-SAPO 34 manufacture was examined. The synthesis mixture was prepared as in Example 3, except that sufficient nickel nitrate (Ni(NO₃)₂6H₂O, Fluka) was added to Solution A to give a synthesis mixture of molar composition:

Al₂O₃:P₂O₅:0.3 SiO₂:0.0075 NiO:TEAOH:1.6 DPA:50 H₂O.

The mixture was divided into two parts, one being seeded with CHA slurry, 6.4 % solids content, to a seeding level of 409 ppm. The seeded and unseeded samples were each heated in a stainless steel autoclave for 60 hours at 175°C. After cooling, the products were recovered, washed, and dried at 120°C. In both cases, a pure SAPO-34 phase was recovered, with molar chemical constitutions and crystal sizes as follows:

15 Unseeded: Al_2O_3 : 0.88 P_2O_5 : 0.36 SiO_2 : 0.0040 NiO_5 , 1 to 10 um

ι το το μιπ

Seeded: $Al_2O_3: 0.84 P_2O_5: 0.31 SiO_2: 0.0042 NiO,$

0.2 to $1.5~\mu m$.

20

5

Again, the benefit of seeding in producing smaller crystals is apparent.

The two samples made as described above were examined by diffuse reflectance FTIR to establish their crystal quality and Broensted acidity. The IR spectra were obtained in a conventional high temperature DRIFT cell using KBr diluted samples (about 4 % sample in dry KBr), the samples being dehydrated before testing at 200 to 300°C under vacuum. The spectra, obtained using 64 scans at 4 cm⁻¹ resolution, were analysed using Gaussian-Lorentzian peaks to determine locations and relative areas and shapes.

15

25

The spectra of the seeded and unseeded products of the example were inspected in the region between wave numbers 1400 and 1000cm⁻¹ and the main peaks attributable to framework T-O stretching were measured. In the Table below are set out the centre locations, peak heights and peak widths (C, H, W) of 5 the three main bands in the region.

C, H, W C. H. W C, H, W Seeded 1106/8.7/51 1135/12.3/54.7 1179/6.7/65.5 Unseeded 1082/1.4/90 1129/2.1/71 1190/0.9/90.6

The seeded sample has, as is apparent from the Table, by far the highest and sharpest peaks, and hence the highest internal crystallinity.

The sole figure of the accompanying drawings shows the region between wave numbers 3800 and 3450 cm⁻¹.

Referring now to the figure, the locations, heights and widths of the main peaks attributable to the bridged hydroxyl groups are shown for the samples. The band at ≈3620 is attributed to undisturbed Broensted OH groups in 8-membered rings while that at ≈3595 is attributed to such OH groups interacting with framework oxygen or OH groups located in the 6-membered rings. Measurement 20 of the contribution (by area) of these bands to the total area in the OH region gives the results in the Table below:

> Sample % Area Contribution Seeded 62 Unseeded 2.1

Clearly, the seeded sample has the higher percentage area contribution from the Broensted acid sites, despite the fact that this sample has a lower particle size, and hence a larger surface/volume ratio. From this it is tentatively

concluded that the remaining peaks in the 3800 to 3620 cm⁻¹ range are associated with internal defects rather than surface hydroxyl groups, and postulated that products with high percentage area contribution of Broensted acid OH groups to the total OH area are materials with a high level of internal crystal perfection.

Example 6

5

This example illustrates the use of CHA seeds in the manufacture of SAPO-34 with a silicon content different from that of Example 3. The synthesis solution was prepared as described in Example 3, but with components in proportions to give the following molar composition:

Al2O3: P2O5: 0.1 SiO2: TEAOH: 1.6 DPA: 52 H2O.

A slurry of 6.4 % solids content of CHA seeds was added to give a seed content of 397 ppm.

The mixture was hydrothermally treated as described in Example 3, and the product recovered in the same way. It was pure SAPO-34, with most crystals in the range 0.2 to 1.5 μ m, with a few crystals of size in the 2 to 4 μ m range also present. The product analysed as

 $Al_2O_3: 0.79 P_2O_5: 0.21 SiO_2.$

Example 7

2.5

Example 6 was repeated, except that the silica content was varied to give a molar composition of the synthesis mixture of:

 $Al_2O_3:P_2O_5:0.45\ SiO_2:TEAOH:1.6\ DPA:52\ H_2O$ with 397 ppm CHA seeds.

The hydrothermal treatment was as described in Example 3; the product was pure SAPO-34 of particle size between 0.2 and 1.5 µm. Chemical analysis:

Al2O3: 0.92 P2O5: 0.42 SiO2.

10

5

The yields from Examples 6 and 7, and the static seeded part of the second part of Example 3, the synthesis mixtures of which differed primarily in their silicon contents, were as follows:

15

Example 6, 0.1 SiO₂; yield 7.8 % 3, 0.3 SiO₂; yield 12.5 % 7, 0.45 SiO₂; yield 12.7 %.

20 Comparative Example B

In Examples 5 to 7, hydrothermal treatment was carried out in a static autoclave. In this and following examples, the influences of stirring and tumbling on the properties of SAPO-34 were examined, this example employing an unseeded synthesis mixture of a molar composition similar to that of the second part of Example 3, but with 51 moles of H₂O rather than 52. Hydrothermal treatment was carried out by heating the synthesis mixture in a stainless steel autoclave from room temperature to 175°C over 6 hours, with stirring at 120 rpm, and maintained at 175°C for 60 hours with continued stirring. Recovery was as

described in Example 3. The product was a mixture of SAPO-34, SAPO-18, with some SAPO-5, the crystals being within the range of 0.2 to 1 μ m.

Example 8

5

This example illustrates the effect of stirring an Offretite seeded synthesis mixture during hydrothermal treatment. Colloidal (<100 nm) Offretite seeds were added from a 5.36 % solids content Offretite slurry, the resulting molar composition of the seeded mixture being:

10

 $Al_2O_3: P_2O_5: 0.3\ SiO_2: TEAOH: 1.6\ DPA: 54\ H_2O$ plus 0.19 weight % seeds.

The synthesis mixture was divided into two parts. One part (A) was

placed in a stainless steel autoclave equipped with a 120 rpm stirrer and heated
from room temperature to 175°C over 6 hours with stirring, and maintained at

175°C for 60 hours with continued stirring. A second part (B) was heated
without stirring from room temperature to 175°C over 2 hours, and maintained at

175°C for 48 hours, with a sample (C) being taken at 24 hours. After recovery

and drying, the products were analysed by SEM and XRD.

Sample A : SAPO-34, contaminated with SAPO-18 and some SAPO-5, crystals between 0.2 and 1.0 $\mu m.$

Sample B: Pure SAPO-34, with crystal size 0.5 to 2 µm.

 $Sample\ C: SAPO-34\ with some\ amorphous\ material,\ crystals\ between\ 0.2$ 25 and 1.5 μm .

Example 9

This example illustrates the effect on Ni-SAPO-34 manufacture of agitation during the warm-up period of hydrothermal treatment, followed by static heat-soaking. A nickel-containing synthesis mixture was prepared, following the procedure described in Example 4, to produce a mixture of molar composition:

Al₂O₃:P₂O₅:0.3 SiO₂:0.0076 NiO:TEAOH:1.6 DPA:52 H₂O.

10

The mixture was divided into two parts, of which one, sample A, was seeded with the CHA seeding slurry used in Example 5 to give a seed content of 202 ppm, the other, sample B, remaining unseeded. Both samples were transferred to stainless steel autoclaves, which were placed in an oven and mounted on a horizontal shaft rotatable at 60 rpm. The autoclaves were tumbled for a 2 hour period of heating to 175°C; tumbling then ceased and the temperature kept at 175°C for 60 hours.

After cooling, the products were recovered by centrifugation, washed, and dried at 120°C. XRD showed that both products were pure Ni-SAPO-34.

20 Sample A comprised crystals of particle size about 1 µm, with damaged surfaces.

Sample B comprised crystals of size ranging up to 10 $\mu\text{m},$ many crystals being fragmented.

The example shows that seeding is required to bring the particle size down to the desired levels even with initial tumbling.

25

Example 10

This example illustrates the use of a SAPO-34 seed slurry in SAPO-34 manufacture

To a synthesis mixture of the molar composition set out in the second part of Example 3 was added a 10% slurry of SAPO-34, prepared as described in the second part of Example 3 with tumbling, to give a seeding level of 0.1% (1000 ppm). The seeded mixture was heated in a stainless steel autoclave at 175°C for 48 hours. The mixture was allowed to cool, and the product recovered and identified as pure SAPO-34 with crystal sizes ranging from 0.5 to 4 µm. The example illustrates that while colloidal SAPO-34 crystals are effective in SAPO-34 manufacture they are not as effective as CHA or LEV structure type zeolite seeds.

10

Example 11

In this example the effectiveness in catalysing the methanol to olefin conversion of the products made and discussed in Example 5 was measured. In a bench scale fixed bed reactor maintained at 450°C methanol diluted with nitrogen (total pressure-atmospheric, partial pressure of methanol 0.12) was passed over a catalyst at WHSV (based on methanol) of 1 hr⁻¹ and a GHSV (based on methanol plus nitrogen) of about 5500 hr⁻¹. After 1 hour on stream at 100 % methanol conversion, the results were as shown in the Table.

Example 5

2.0

	Yield, %	Seed	ed	Unseeded	l
	C ₂ =	50.1			47.9
25	C ₃ =	28.0)		33.4
	$C_2 = + C_3 = + C_3$	4=	85.6	91.4	
	C ₁ to C ₄ sats.		11.0	6.1	

Example 5

The yield of the more desirable ethylene is increased by about 5% using the product obtained with seeding compared with the unseeded product.

20

WE CLAIM:

- A process for the manufacture of a crystalline molecular sieve containing phosphorus in its framework, which process comprises treating a synthesis
 mixture comprising elements necessary to form the phosphorus-containing molecular sieve and colloidal crystalline molecular sieve seeds for a time and at a temperature appropriate to form the desired molecular sieve.
- A process as claimed in claim 1, wherein the phosphorus-containing molecular sieve is selected from aluminophosphates and silicaaluminophosphates.
 - A process as claimed in claim 1, wherein the phosphorus-containing molecular sieve is of the CHA or LEV structure type.
 - A process as claimed in claim 1, wherein the phosphorus-containing molecular sieve is SAPO-34.
- A process as claimed in claim 4, wherein the SAPO-34 is Ni-SAPO-34.
 - A process as claimed in claim 4, wherein the percentage area contribution of Broensted acid sites to the total OH area in the IR spectrum is at least 30%.
- A process as claimed in claim 6, wherein the said contribution is at least
 50%.
 - A process as claimed in claim 1, wherein the seeds are of structure type LEV, OFF, or CHA.

25

- A process as claimed in claim 1, wherein the seeds are of Levyne, ZSM-45, Chabasite, Offretite, or SAPO-34.
- A process as claimed in claim 1, wherein the seeds are present in a
 proportion within the range of 1 to 2000 ppm, based on the total weight of the synthesis mixture.
 - 11. A process as claimed in claim 10, wherein the proportion is within the range of from 100 to 1500 ppm.
 - 12. A process as claimed in claim 10, wherein the proportion is within the range of from 100 to 250 ppm.
- A process as claimed in claim 1, wherein the seeds are incorporated in the
 synthesis mixture in the form of a suspension.
 - 14. A process as claimed in claim 1, wherein the particle size of the seeds is within the range of from 5 to 1000 nm.
- 20 15. A process as claimed in claim 14, wherein the particle size is within the range of from 10 to 300 nm.
 - 16. A process as claimed in claim 14, wherein the particle size is within the range of from 20 to 100 nm.
 - 17. A process as claimed in claim 1, wherein the phosphorus-containing molecular sieve is of a first structure type and the seeds are of a second structure type.

10

- 18. A process as claimed in claim 17, wherein the first structure type is CHA and the second structure type is LEV.
- 19. The molecular sieve product of the process as claimed in claim 1.
- The molecular sieve of claim 19, in particulate or layer form.
- SAPO-34 in which the percentage area contribution of Broensted acid sites to the total OH area in the IR spectrum is at least 30%.
- A process for the conversion of an oxygenate to olefins which comprises contacting the oxygenate under catalytic conversion conditions with the molecular sieve of claim 19.
- 15 23. A process of hydrocarbon conversion, adsorption or separation employing the molecular sieve of claim 19, if desired after washing, cation exchange, or calcining.
- 24. In a synthesis of a phosphorus-containing crystalline molecular sieve, the improvement which comprises the use of colloidal crystalline molecular sieve seed crystals to effect at least one function selected from the control of the particle size of the product and the acceleration of the formation of the product.

ABSTRACT

5 PROCESSES FOR MANUFACTURE OF MOLECULAR SIEVES

Colloidal crystalline molecular sieve seeds are used in phosphoruscontaining crystalline molecular sieve manufacture. Certain of the products have 10 enhanced utility in oxygenate conversions.

It is well-known that seeding a molecular sieve synthesis mixture frequently has beneficial effects, for example in controlling the particle size of the product, avoiding the need for an organic template, accelerating . synthesis, and improving the proportion of product that is of the intended structure type.

In U.S. Patent No. 4 440 871, the preparation of a number of phosphorus-containing molecular sieves is described, and it is stated that the crystallization procedure may be facilitated by stirring, or other moderate 20 agitation of the synthesis mixture, or by seeding it with crystals of the molecular sieve to be produced or one of a topologically similar structure.

The patent particularly describes processes for the manufacture of numerous crystalline microporous

25 silicoaluminophosphates (SAPO's) including SAPO-34, employing sources of silicon (e.g., a silica sol), aluminium (e.g., hydrated aluminium oxide), and phosphorus (e.g., orthophosphoric acid), and an organic template, for example tetraethylammonium hydroxide (TEAOH), isopropylamine (iPrNH2)

30 or di-n-propylamine (DPA). The patent, the disclosure of which is incorporated by reference herein, gives X-ray diffraction data for the SAPO's and describes their utilities in catalysis and absorption.

COPYREDOV LOGGEOUS

It has now been found that advantages result from the use of colloidal seeds in the manufacture of phosphorus-containing molecular sieves.

The present invention accordingly provides in a first

5 aspect a process for the manufacture of a crystalline
molecular sieve containing phosphorus in its framework, which
process comprises treating a synthesis mixture comprising
elements necessary to form the phosphorus-containing
molecular sieve and colloidal crystalline molecular sieve

10 seeds for a time and at a temperature appropriate to form the
desired molecular sieve.

It has surprisingly also been found that the seed crystals may be of a structure type different from that of the desired molecular sieve. Such seeding may be regarded as "heterostructural", whereas seeding with seeds of the same structure type is termed "isostructural", whether or not the seeds are of the same composition (i.e., contain the same elements in the same proportions) as the crystalline molecular sieve to be produced.

Where the seeds are of a structure type different from those of the desired molecular sieve, advantageously the seeds and the desired molecular sieves are topologically similar, for example are members of the ABC-6 group of materials, as described in "Topochemistry of Zeolites and 25 Related Materials", J.V. Smith, Chem. Rev. 1988, 88, 149 at 167, the disclosure of which review article is incorporated herein by reference. The ABC-6 group includes, inter alia, the Offretite, Chabazite and Levyne structures.

As used in this specification, the term "structure type"

30 is used in the sense described in the Structure Type Atlas,

Zeolites 17, 1996.

The present invention accordingly provides in a second aspect a process for the manufacture of a crystalline molecular sieve containing phosphorus in its framework, which

25

PCT/GB99/02480 WO 00/06493 3

comprises treating a synthesis mixture comprising elements necessary to form a phosphorus-containing molecular sieve of a first structure type and colloidal molecular sieve seed crystals of a second, different, structure type, for a time 5 sufficient and at a temperature appropriate to form the molecular sieve of the first structure type.

In further aspects, the invention provides the use, in the synthesis of a phosphorus-containing crystalline molecular sieve, of colloidal seed crystals to control the 10 particle size of the product, or to accelerate the formation of the product, or both to control the particle size and accelerate the formation of the product.

As the phosphorus-containing molecular sieves to be prepared by the processes of the invention, there may be 15 mentioned more especially aluminophosphates and silicoaluminophosphates. As examples of structure types produced there may be mentioned more especially molecular sieves of the structure types CHA and LEV. As seeds, there may for example be used crystals of structure type LEV, OFF, 20 and CHA. As specific materials to be used, there may be mentioned Levyne, ZSM-45, Chabasite, Offretite and SAPO-34.

The seeds used in the present invention may be obtained by methods described herein or known in the art or described in the literature.

Manufacture of OFF-structure type seed crystals, in particular colloidal Offretite seeds, may be carried out as described in International Application No. WO 97/03020, while suitable procedures, including details of synthesis mixtures and hydrothermal treatment, for the manufacture of LEV- and 30 CHA- structure type crystals are described in EP-A-91048, 91049, 107 370, 143 642 and U.S. Patent No. 4 495 303 (for LEV) and GB-A-868 846 and 2 061 500 and U.S. Patents Nos. 3 030 181 and 4 544 538 (for CHA), the disclosures of all of which are incorporated by reference herein. Manufacture of

CHA- and LEV-structure type seed crystals is advantageously carried out as described in the examples below.

Apart from the presence of the seeds, the synthesis mixture used in the present invention is typically one that is known in the art or as described in the literature as suitable for the production of the molecular sieve concerned. This is also the case for the conditions of treatment, except that the presence of the seeds may make possible the reduction of reaction times or may obviate stirring if that were otherwise necessary.

In general, the treatment of the synthesis mixture to yield the desired phosphorus-containing crystalline molecular sieve, usually termed hydrothermal treatment, though strictly that term should be used only for treatments in which there 15 is vapour-phase water present, is advantageously carried out under autogenous pressure, for example in an autoclave, for example a stainless steel autoclave which may, if desired, be ptfe-lined. The treatment may, for example, be carried out at a temperature within the range of from 50, advantageously 20 from 90, especially 120, to 250°C, depending on the molecular sieve being made. The treatment may, for example, be carried out for a period within the range of from 20 to 200 hours, preferably up to 100 hours, again depending on the molecular sieve being formed. The procedure may include an ageing 25 period, either at room temperature or, preferably, at a moderately elevated temperature, before the hydrothermal treatment at more elevated temperature. The latter may include a period of gradual or stepwise variation in temperature.

CONTROL CONTRO

30 For certain applications, the treatment is carried out with stirring or with rotating the vessel about a horizontal axis (tumbling). For other applications, static hydrothermal treatment is preferred. If desired, the synthesis mixture may be stirred or tumbled during an initial

part of the heating stage, for example, from room temperature to an elevated, e.g., the final treatment, temperature, and be static for the remainder. Agitation generally produces a product with a smaller particle size and a narrower particle size distribution than static hydrothermal treatment.

The seeds are generally present in the synthesis mixture in a concentration of up to 10000, advantageously at most 3000, more advantageously at most 1500, and preferably at most 1000, more preferably at most 500, and most preferably 10 at most 350 ppm, based on the total weight of the synthesis mixture. A minimum seeding level is generally 1 ppb (0.001 ppm), advantageously at least 0.1, more advantageously at least 1, and preferably at least 10, ppm, based on the total weight of the synthesis mixture. Advantageous ranges of 15 proportions are from 1 to 2000, preferably 100 to 1500, and most preferably 100 to 250, ppm.

The colloidal seeds are advantageously incorporated in the synthesis mixture in the form of a suspension, advantageously in an aqueous medium, preferably water, or 20 another liquid component of the synthesis mixture. Less preferably they may be added in dry, but not calcined, form. It is believed that calcination significantly reduces the activity of small crystallites to act as seeds; similarly any other treatment that reduces the seeding activity of 25 materials should be avoided. As used herein, the term "colloidal", when used of a suspension, refers to one containing discrete finely divided particles dispersed in a continuous liquid phase and preferably refers to a suspension that is stable, in the sense that no visible separation 30 occurs or sediment forms, in a period sufficient for the use intended, advantageously for at least 10, more advantageously at least 20, preferably at least 100, and more preferably at least 500, hours at ambient temperature (23°C).

COTTATON COLLEGE

The maximum size of the particles for the suspension to remain stable (peptized) will depend to some extent on their shape, on the nature and pH of the continuous medium, as well as on the period during which the suspension must remain

5 usable. In general, the maximum dimension will be 1µm, advantageously 500, more advantageously 400, preferably 300, more preferably 200, and most preferably 100, nm. The particles may be of spherical, columnar, rod, coffin, platelet, or needle shapes. Where particles are platelets or 10 needles, the dimension referred to is their smallest dimension.

The minimum dimension is such that the particles do not dissolve or re-dissolve in the medium, and for crystallinity they must contain at least a small plurality, advantageously at least two, preferably four, unit cells of the crystal. The minimum particle size is in general 5, advantageously 10, and preferably 20, nm. Mean particle sizes are generally in the range 5 to 1000, advantageously 10 to 300, more advantageously 10 to 200, and preferably 20 to 100, nm.

20 Advantageously at least 50%, more advantageously at least 80%, and more preferably at least 95%, by number, of the particles are greater than the given minima, smaller than the given maxima, or within the given ranges of particle size. Measurements of particle size may be effected by electron microscopy, for example using a Philips SEM 515 unit.

If the product is desired in small particle size form, a larger number of smaller sized seeds is desirably employed. The smaller the particle size of the seeds, the lower the weight percentage that is effective. The crystals are advantageously stirred into the synthesis mixture for a time sufficient to provide a uniform dispersion, this time being dependent primarily on the viscosity of the synthesis mixture, and also on the scale and type of the equipment, but ranging generally from 30 seconds to 10 minutes.

More especially, the invention provides processes and uses in which colloidal LEV structure type seeds are used in the manufacture of a phosphorus-containing crystalline molecular sieve.

A colloidal suspension of LEV may be obtained by synthesizing a LEV structure type molecular sieve by hydrothermal treatment of an appropriate synthesis mixture, and separating the product from the synthesis mixture, washing the product, and recovering the resulting wash lo liquid.

Examples of the LEV structure type include Levyne, NU-3, ZK-20, ZSM-45 and SAPO-35.

The colloidal LEV seeds are especially suitable to provide crystalline molecular sieves of the CHA structure

15 type. Examples of such CHA materials are SAPO-, AlPO-, MeAPO-, MeAPSO-, ElAPSO- and ElAPO -47 and especially the corresponding -34 materials. In these formulae, El represents magnesium, zinc, iron, cobalt, nickel, manganese, chromium or mixtures of any two or more such elements. CHA

20 structure type seeds may also be used in synthesis of these materials. LEV and CHA structure type seeds may be used in the synthesis of SAPO-, AlPO-, MeAPO-, MeAPSO-, ElAPSO- and ElAPO- materials of the LEV structure type, e.g., the -35 materials. Where a material is referred to as, for example, a

25 SAPO material, this terminology includes the possibility that additional elements may be present, either in the framework or otherwise, as in the case discussed below, of Ni-SAPO.

Among these materials, SAPO-34 has been found to have considerable utility in catalysing the conversion of methanol to light olefins, primarily those with 2 to 4 carbon atoms (see, for example, U.S. Patent No. 5 126 308, also incorporated by reference herein). It would be of value to be able to increase the proportion of ethylene in the product.

CONTROL CONTROL

The present invention accordingly also provides a process for the manufacture of SAPO-34 in which the percentage area contribution of Broensted acid sites to the total OH area in the IR spectrum is at least 30%,

5 advantageously at least 50%, and preferably at least 60%, by a procedure in which the synthesis mixture contains colloidal crystalline molecular sieve crystals. In certain embodiments, percentage area contribution is at most 95%.

More especially, the invention further provides a

10 process for the manufacture of SAPO-34, which comprises
treating a synthesis mixture having a molar composition
appropriate for SAPO-34 formation and also containing
colloidal OFF-type, CHA-type, or LEV-type seed crystals,
advantageously of mean particle size of at most 400 nm, for a

15 time and at a temperature sufficient to form SAPO-34.

The process of the invention is capable of providing SAPO-34 in which the particle size is at most 0.75 μm , advantageously at most 0.5 μm . Advantageously the particle size distribution is such that 80 % (by number) of the 20 particles are within ± 10 % of the mean.

In a further aspect, the invention provides a process for the conversion of an oxygenate, especially methanol, to olefins which comprises contacting the oxygenate with a catalyst under conversion conditions, the catalyst comprising 25 SAPO-34 produced in accordance with the invention.

The olefins produced are advantageously light olefins, by which is to be understood an olefin mixture of which at least 50% by weight contain from 2 to 4 carbon atoms.

Referring now more especially to the Broensted acid site aspect of the invention, it is believed (without the invention being limited by any theoretical considerations) that the Broensted acidity is important in the catalytic activity, especially in oxygenate to olefin conversion, of a molecular sieve, and that a molecular sieve in which the

bridged hydroxyl groups represent a high proportion of the hydroxyl groups in the crystal will have a high activity. Infra-red analysis of a highly active product of the invention (described as are the methods of measurement in 5 more detail in the Examples below) shows that in the SAPO-34 OH region, 4000 to 3000 cm⁻¹, two peaks, at ~3620 and ~3595 cm⁻¹, are the main features, while less active samples show a number of bands in the range from 3750 to 3620 cm⁻¹, which are assigned to Al-OH, Si-OH, and P-OH groups on an external surface or on an internal defect.

A further IR spectrum characteristic associated with catalytic activity is a high peak intensity in the T-O asymmetric stretch region, at 1050 to 1150 cm⁻¹, intensity being indicated by both height and sharpness, i.e., a high 15 level of internal crystallinity. It is accordingly believed that a correlation exists between high internal crystallinity, or crystal perfection, and a high contribution of Broensted OH groups to the total OH content of the material.

Further, in common with many other molecular sieves, the catalytic activity and stability of activity of SAPO-34 are in general terms greater the smaller the particle size.

The synthesis mixture for producing SAPO-34 according to the invention advantageously has a molar composition, apart 25 from the colloidal seeds, within the following ranges:

 P_2O_5 : Al_2O_3 0.9 to 1.2 : 1 SiO₂ : Al_2O_3 0.05 to 0.4 : 1 H_2O : Al_2O_3 10 to 100 : 1

30

20

together with an organic template, advantageously tetraethylammonium hydroxide (TEAOH), dipropylamine (DPA), isopropylamine or morpholine, or a mixture of two or more WO 00/06493 PCT/GB99/02480

such templates, in a proportion appropriate to yield SAPO-34. A preferred template mixture comprises TEAOH and DPA.

In a particularly advantageous embodiment of the invention the synthesis mixture advantageously contains a source of metallic elements, especially a Group VIII metal, more especially nickel. A convenient source of the metal is a water-soluble salt, for example the nitrate. The metal is advantageously present in a molar proportion calculated as oxide relative to Al₂O₃ within the range of 0.001 to 0.05, preferably 0.005 to 0.01. The presence of nickel enhances the catalytic activity at least in oxygenate conversion. Other suitable Group VIII metals include Fe and Co, while other suitable metals include Mn, Cr, Cu, Zn, Mg, Ti and Zr.

The sources of the materials may be any of those in 15 commercial use or described in the literature, as may the preparation of the synthesis mixture.

The invention also provides the products of the processes and of the uses of the earlier aspects of the invention. The products, if required after cation exchange 20 and/or calcining, have utility as catalyst precursors, catalysts, and separation and absorption media. They are especially useful in numerous hydrocarbon conversions. separations and absorptions. They may be used alone, or in admixture with other molecular sieves, in particulate form, 25 supported or unsupported, or in the form of a supported layer, for example in the form of a membrane, for example as described in International Application WO 94/25151. Hydrocarbon conversions include, for example, cracking, reforming, hydrofining, aromatization, oligomerisation, 30 isomerization, dewaxing, and hydrocracking (e.g., naphtha to light olefins, higher to lower molecular weight hydrocarbons, alkylation, transalkylation, disproportionation or isomerization of aromatics). Other conversions include the

20

reaction of alcohols with olefins and the conversion of oxygenates to hydrocarbons.

Conversion of oxygenates may be carried out with the oxygenate, e.g., methanol, in the liquid or, preferably, the vapour phase, in batch or, preferably, continuous mode. When carried out in continuous mode, a weight hourly space velocity (WHSV) based on oxygenate, of advantageously 1 to 1000, preferably 1 to 100, hour may conveniently be used. An elevated temperature is generally required to obtain economic conversion rates, e.g., one between 300 and 600°C, preferably from 400 to 500°C, and more preferably about 450°C. The catalyst may be in a fixed bed, or a dynamic, e.g., fluidized or moving, bed.

The oxygenate feedstock may be mixed with a diluent,

inert under the reaction conditions, e.g., argon, nitrogen,
carbon dioxide, hydrogen, or steam. The concentration of
methanol in the feedstream may vary widely, e.g., from 5 to
90 mole per cent of the feedstock. The pressure may vary
within a wide range, e.g., from atmospheric to 500 kPa.

The following Examples, in which parts are by weight unless otherwise indicated, illustrate the invention. The source and purity of starting materials are those first given, unless indicated otherwise.

25 Example 1

This example illustrates the manufacture of a LEV-type zeolite of particle size suitable for use as seeds in the manufacture, inter alia, of phosphorus-containing crystalline 30 molecular sieves.

In a first stage, 15.95 parts of sodium aluminate (Dynamit Nobel, 53 % Al_2O_3 , 41 % Na_2O_3 , 6 % $H_2O)$, 19.95 parts of sodium hydroxide (Baker, 98.6 %) and 5.58 parts of potassium hydroxide (Baker, 87.4 %) were dissolved in 151.06

WO 00/06493 PCT/GB99/02480

parts of water, and heated to boiling until a clear solution was obtained. After cooling to room temperature, water loss was compensated, to form Solution A. 270.60 parts of colloidal silica (Ludox HS40, 40 % SiO₂) were mixed with 5 106.12 parts of choline chloride (R, Fluka) forming a viscous mass, and Solution A added with stirring at increasing speed as the viscosity decreased, together with 190 parts of rinse water, mixing then continuing for a further 5 minutes. The molar composition was:

10

1.95 Na₂O:0.24 K₂O:0.46 Al₂O₃:10 SiO₂:4.187 R:155 H₂O.

To 290 parts of this mixture, 0.49 parts of conventional LEV zeolite seeds were added, and a sample transferred to an 15 autoclave, where it was heated in a 120°C oven for 144 hours. The product was washed, recovered by centrifuging and dried overnight at 120°C. The product comprised spherical aggregates of from 2 to 2.5 µm, made up of ~100 nm particles, with an X-ray diffraction pattern (XRD) of ZSM-45, a zeolite 20 of LEV-type structure, as described in EP-A-107 370 (Mobil).

The product was used as seeds in the next stage, in which 8.38 parts of sodium aluminate, 10.53 parts of sodium hydroxide, 2.96 parts of potassium hydroxide, and 78.95 parts of water were treated as described above to form a Solution 25 A. Solution A was then added to a mixture of 142.42 parts of colloidal silica and 55.5 parts of choline chloride, together with 100.00 parts of rinse water and mixed as described above, with the addition of 0.68 parts of the first stage seeds. The reaction mixture was heated in an 30 autoclave at 120°C for 174 hours, the product recovered by washing, centrifuging and drying having an XRD similar to The second supernatant of the that of the first stage. washing procedure was not clear, and had a pH of 10.3. was found to be a dispersion with a solids content of 2.3 %.

Analysis by scanning electron microscopy (SEM) and XRD showed $\sim 100~\rm nm$ unaggregated crystals with a ZSM-45 structure, LEV structure type.

5 Example 2

This example illustrates the manufacture of a chabasite dispersion suitable for use, in turn, for seeding in SAPO-34 manufacture. The seeds were prepared as follows:

A synthesis mixture was prepared as described in the first part of Example 1, except that as seeds the colloidal sol from the second supernatant of the second part of Example 1 was used, at a seeding level of 0.15% by weight of solids. The seeded synthesis mixture was heated in a stainless steel autoclave for 96 hours at 120°C, with a heat-up time of 3 hours. The product, recovered by centrifuging and drying, had an XRD pattern corresponding to ZSM-45. The first supernatant was not clear and yielded, after centrifuging at 11000 rpm and further washing, a dispersion with solids content 4.6%, of crystals of size about 100 nm, XRD showing the product to be ZSM-45, a LEV structure-type zeolite.

Solution A was prepared as described in Example 1 using the following components, in the proportions shown:

25	. наОН	61.66
	KOH	28.73
	Al(OH) ₃ (Alcoa, 99.3 %)	15.73
	H ₂ O	190.30

30 300.23 parts of colloidal silica and 168.89 parts of water were poured into a mixer, and Solution A added together with 12.65 parts of rinse water. After mixing for 5 minutes, 16 parts of the 4.6 % solids LEV slurry were added.

The molar composition of the synthesis mixture was:

 $3.8\ Na_2O\!:\!1.12\ K_2O\!:\!0.5\ Al_2O_3\!:\!10\ SiO_2\!:\!161\ H_2O,$ with 927 ppm seeds.

5

The synthesis mixture was heated in an autoclave to 100°C over 2 hours, and maintained at that temperature for 96 hours. After cooling, the content of the autoclave, a milky suspension, was washed five times with demineralized water 10 and centrifuged at 9000 rpm. After taking a sample for XRD and SEM, the remainder was redispersed to form a colloidal solution, stable over several days, with a solids content of 6.4 %. The XRD of the product shows it to be chabasite, with a uniform particle size 100 x 400 nm.

15

20

Example 3

This example illustrates the manufacture of SAPO-34 of small particle size and uniform size distribution.

A synthesis mixture was prepared from the following components in the proportions shown.

	WO 00/06493	15	PCT/GB99/02480
	Solution	Component	Proportion
	A	Al ₂ O ₃ (Pural SB Condea 75%)	68.18
		H ₂ O	100.02
5	В	H ₃ PO ₄ (Acros, 85%)	115.52
		H ₂ O,	80.27
	С	Colloidal Silica (Ludox AS40)	22.73
		H ₂ O, rinse	10.20
10			
	D	TEAOH (Eastern Chemical, 40%)	182.85
	E	DPA (Fluka)	80.23
15	F	Seeds, 4.6 Wt.% LEV	31.95

Slurry A was prepared in a mixer, and Solution B added, when a viscous solution resulted. After leaving the solution to rest for 2 minutes, 26.84 parts of rinse water were added.

20 After mixing the paste for 6 minutes, C was added, and mixed for 2 minutes before adding Solution D. Upon adding E with 70.72 parts of rinse water two phases were formed. After a further 3 minutes mixing a visually homogeneous solution resulted and after a further 10 minutes mixing the seeds F

25 were added. The molar composition was:

Al₂O₃:P₂O₅:0.3 SiO₂:TEAOH:1.6 DPA:56 H₂O. + 1860 ppm by weight LEV seeds.

30 The seeded gel was heated for 60 hours at 175°C in a stainless steel autoclave. The solid product was recovered by centrifugation, washed 11 times with water to a conductivity of about 18 µs/cm, and dried at 120°C. XRD and SEM showed a pure SAPO-34 product with crystals between 0.2

WO 00/06493 16 PCT/GB99/02480

and 1.3 μm , with a few crystals between 2 and 3 μm . Chemical analysis indicated a product of molar composition:

$$Al_2O_3$$
: 0.99 P_2O_5 : 0.36 SiO_2 .

5

In a similar manner a synthesis mixture was prepared from the following components in the proportions shown.

	Solution	Component	Proportion
10	A	Al ₂ O ₃ (Pural SB Condea 75 %)	68.06
		H ₂ O	100.15
15	В	H ₃ PO ₄ (Acros, 85 %)	115.74
		$\rm H_2O$, including rinse	104.92
20	C	Colloidal Silica (Ludox AS40)	22.50
		H ₂ O, rinse	10.20
25	D	TEAOH (Eastern Chemical, 40 %)	183.31
		H ₂ O, rinse	43.17
30	E	DPA (Fluka)	80.79
		H_2O , rinse .	26.27

Slurry A was prepared in a mixer, and Solution B added,

when a viscous mixture resulted. After mixing for 6
minutes, Solution C was added, and mixed for 2 minutes before
adding Solution D which was mixed in for 5 minutes. When E
was added, two phases were formed. After a further 15
minutes mixing a visually homogeneous mixture resulted. The

do molar composition was:

Al₂O₃:P₂O₅:0.3 SiO₂:TEAOH:1.6 DPA:52 H₂O.

The synthesis solution was divided, and to one sample a 6.4 % slurry of CHA zeolite, prepared as described in Example 2, was added to give a seeding level 410 ppm, the other 5 sample remaining unseeded.

The unseeded sample was heated in a stainless steel autoclave at 175°C for 60 hours. The seeded sample was divided, one part being heated, without stirring, in a ptfelined autoclave for 60 hours at 175°C, and the other being 10 heated with tumbling in a stainless steel autoclave for 60 hours at 175°C.

The samples were allowed to cool, and the product recovered by washing and drying at 120°C. In all cases, a pure SAPO-34 product was obtained, with a molar chemical constitution and crystal sizes as follows:

Unseeded: Al₂O₃ : 0.91 P₂O₅ : 0.33 SiO₂, 1 to 10 μm

Seeded,

20 static: Al_2O_3 : 0.89 P_2O_5 : 0.31 SiO_2 , 0.2 to 1.5 μm

Seeded.

tumbled: Al_2O_3 : 0.91 P_2O_5 : 0.35 SiO_2 , ~0.5 μm .

25 The benefits of reduced crystal size and size distribution of seeding with colloidal chabasite seeds are apparent, especially when combined with tumbling.

Example 4

30

This example illustrates the use of colloidal Offretite seeds in the manufacture of SAPO-34. The colloidal Offretite was prepared as described in Example 2 of WO

97/03020. A synthesis mixture was prepared as described in Example 3, with the following molar composition:

Al₂O₃ : P₂O₅ : 0.3 SiO₂ : TEAOH : 1.6 DPA : 51 H₂O.

5

To this was added a portion of a 5.36 % solids content colloidal offretite slurry (crystal size below 100 nm) to give a seeding level of 203 ppm. Hydrothermal treatment and product recovery were carried out as described in Example 3.

10 The product obtained was pure SAPO-34, the particle size of crystals being mainly between 0.2 and 1.3 µm, with a few crystals between 2 and 3 µm present.

Comparative Example A

15

This example illustrates the use of powdered LEV, contaminated with some Offretite, in SAPO-34 manufacture. To the same synthesis mixture prepared for use in Example 4 were added a LEV powder in a proportion to give a seed level 20 of 217 ppm. The powder was mixed into the synthesis mixture gel by shaking the gel in a polypropylene bottle for 2 minutes. Hydrothermal treatment and product recovery were carried out as described in Example 4. The product was pure SAPO-34, with the majority of the crystals of size between 25 0.5 and 2.5 µm. Comparison of this example with Example 4 shows that colloidal seeds at approximately the same weight ratio yield smaller crystals.

Example 5

30

In this example, the effect of seeding on Ni-SAPO 34 manufacture was examined. The synthesis mixture was prepared as in Example 3, except that sufficient nickel nitrate (Ni(NO₃) $_2$ 6H $_2$ O, Fluka) was added to Solution A to

15

20

give a synthesis mixture of molar composition:

Al₂O₃:P₂O₅:0.3 SiO₂:0.0075 NiO:TEAOH:1.6 DPA:50 H₂O.

The mixture was divided into two parts, one being seeded with CHA slurry, 6.4 % solids content, to a seeding level of 409 ppm. The seeded and unseeded samples were each heated in a stainless steel autoclave for 60 hours at 175°C. After cooling, the products were recovered, washed, and dried at 120°C. In both cases, a pure SAPO-34 phase was recovered, with molar chemical constitutions and crystal sizes as follows:

Unseeded: Al_2O_3 : 0.88 P_2O_5 : 0.36 SiO_2 : 0.0040 NiO,

l to 10 μm

Seeded: Al_2O_3 : 0.84 P_2O_5 : 0.31 SiO_2 : 0.0042 NiO_7 0.2 to 1.5 μm .

Again, the benefit of seeding in producing smaller crystals is apparent.

The two samples made as described above were examined by diffuse reflectance FTIR to establish their crystal quality and Broensted acidity. The IR spectra were obtained in a conventional high temperature DRIFT cell using KBr diluted samples (about 4 % sample in dry KBr), the samples being dehydrated before testing at 200 to 300°C under vacuum. The spectra, obtained using 64 scans at 4 cm⁻¹ resolution, were analysed using Gaussian-Lorentzian peaks to determine 30 locations and relative areas and shapes.

The spectra of the seeded and unseeded products of the example were inspected in the region between wave numbers 1400 and 1000cm⁻¹ and the main peaks attributable to framework T-O stretching were measured. In the Table below are set out

the centre locations, peak heights and peak widths (C, H, W) of the three main bands in the region.

C, H, W C, H, W C, H, W

Seeded 1106/8.7/51 1135/12.3/54.7 1179/6.7/65.5
Unseeded 1082/1.4/90 1129/2.1/71 1190/0.9/90.6

The seeded sample has, as is apparent from the Table, by far the highest and sharpest peaks, and hence the highest 10 internal crystallinity.

The sole figure of the accompanying drawings shows the region between wave numbers 3800 and 3450 $\mbox{cm}^{\text{-1}}.$

Referring now to the figure, the locations, heights and widths of the main peaks attributable to the bridged hydroxyl groups are shown for the samples. The band at \$3620 is attributed to undisturbed Broensted OH groups in 8-membered rings while that at \$3595 is attributed to such OH groups interacting with framework oxygen or OH groups located in the 6-membered rings. Measurement of the contribution (by area) of these bands to the total area in the OH region gives the results in the Table below:

Sample % Area Contribution
Seeded 62
Unseeded 21

Clearly, the seeded sample has the higher percentage area contribution from the Broensted acid sites, despite the fact that this sample has a lower particle size, and hence a larger surface/volume ratio. From this it is tentatively concluded that the remaining peaks in the 3800 to 3620 cm⁻¹ range are associated with internal defects rather than surface hydroxyl groups, and postulated that products with high percentage area contribution of Broensted acid OH groups

to the total OH area are materials with a high level of internal crystal perfection.

Example 6

5

This example illustrates the use of CHA seeds in the manufacture of SAPO-34 with a silicon content different from that of Example 3. The synthesis solution was prepared as described in Example 3, but with components in proportions to give the following molar composition:

Al₂O₃ : P₂O₅ : 0.1 SiO₂ : TEAOH : 1.6 DPA : 52 H₂O.

A slurry of 6.4 % solids content of CHA seeds was added 15 to give a seed content of 397 ppm.

The mixture was hydrothermally treated as described in Example 3, and the product recovered in the same way. It was pure SAPO-34, with most crystals in the range 0.2 to 1.5 μm , with a few crystals of size in the 2 to 4 μm range also present. The product analysed as

Example 7

25

Example 6 was repeated, except that the silica content was varied to give a molar composition of the synthesis

20

mixture of:

 $\label{eq:Al2O3} Al_2O_3~:~P_2O_5~:~0.45~SiO_2~:~TEAOH~:~1.6~DPA~:~52~H_2O$ with 397 ppm CHA seeds.

5

The hydrothermal treatment was as described in Example 3; the product was pure SAPO-34 of particle size between 0.2 and 1.5 μm . Chemical analysis:

10 Al₂O₃ : 0.92 P₂O₅ : 0.42 SiO₂.

The yields from Examples 6 and 7, and the static seeded part of the second part of Example 3, the synthesis mixtures of which differed primarily in their silicon contents, were 15 as follows:

Example 6, 0.1 SiO_2 ; yield 7.8 % 3, 0.3 SiO_2 ; yield 12.5 % 7, 0.45 SiO_2 ; yield 12.7 %.

Comparative Example B

In Examples 5 to 7, hydrothermal treatment was carried out in a static autoclave. In this and following examples, 25 the influences of stirring and tumbling on the properties of SAPO-34 were examined, this example employing an unseeded synthesis mixture of a molar composition similar to that of the second part of Example 3, but with 51 moles of H₂O rather than 52. Hydrothermal treatment was carried out by heating 30 the synthesis mixture in a stainless steel autoclave from room temperature to 175°C over 6 hours, with stirring at 120 rpm, and maintained at 175°C for 60 hours with continued stirring. Recovery was as described in Example 3. The

PCT/GB99/02480

the crystals being within the range of 0.2 to 1 $\mu m.\,$

Example 8

5

15

This example illustrates the effect of stirring an Offretite seeded synthesis mixture during hydrothermal treatment. Colloidal (<100 nm) Offretite seeds were added from a 5.36 % solids content Offretite slurry, the resulting 10 molar composition of the seeded mixture being:

Al₂O₃ : P₂O₅ : 0.3 SiO₂ : TEAOH : 1.6 DPA : 54 H₂O plus 0.19 weight % seeds.

The synthesis mixture was divided into two parts. One part (A) was placed in a stainless steel autoclave equipped with a 120 rpm stirrer and heated from room temperature to 175°C over 6 hours with stirring, and maintained at 175°C for 60 hours with continued stirring. A second part (B) was 20 heated without stirring from room temperature to 175°C over 2 hours, and maintained at 175°C for 48 hours, with a sample (C) being taken at 24 hours. After recovery and drying, the products were analysed by SEM and XRD.

Sample A: SAPO-34, contaminated with SAPO-18 and some 25 SAPO-5, crystals between 0.2 and 1.0 μm.

Sample B : Pure SAPO-34, with crystal size 0.5 to 2µm. Sample C : SAPO-34 with some amorphous material, crystals between 0.2 and 1.5 µm.

30 Example 9

This example illustrates the effect on Ni-SAPO-34 manufacture of agitation during the warm-up period of hydrothermal treatment, followed by static heat-soaking. A nickel-containing synthesis mixture was prepared, following the procedure described in Example 4, to produce a mixture of molar composition:

5 Al₂O₃:P₂O₅:0.3 SiO₂:0.0076 NiO:TEAOH:1.6 DPA:52 H₂O.

The mixture was divided into two parts, of which one, sample A, was seeded with the CHA seeding slurry used in Example 5 to give a seed content of 202 ppm, the other,

10 sample B, remaining unseeded. Both samples were transferred to stainless steel autoclaves, which were placed in an oven and mounted on a horizontal shaft rotatable at 60 rpm. The autoclaves were tumbled for a 2 hour period of heating to 175°C; tumbling then ceased and the temperature kept at 175°C

After cooling, the products were recovered by centrifugation, washed, and dried at 120°C. XRD showed that both products were pure Ni-SAPO-34. Sample A comprised crystals of particle size about 1 µm, with damaged surfaces.

20 Sample B comprised crystals of size ranging up to 10 µm, many crystals being fragmented.

The example shows that seeding is required to bring the particle size down to the desired levels even with initial tumbling.

25

Example 10

This example illustrates the use of a SAPO-34 seed slurry in SAPO-34 manufacture.

To a synthesis mixture of the molar composition set out in the second part of Example 3 was added a 10% slurry of SAPO-34, prepared as described in the second part of Example 3 with tumbling, to give a seeding level of 0.1% (1000 ppm). The seeded mixture was heated in a stainless steel autoclave

at 175°C for 48 hours. The mixture was allowed to cool, and the product recovered and identified as pure SAPO-34 with crystal sizes ranging from 0.5 to 4 μ m. The example illustrates that while colloidal SAPO-34 crystals are 5 effective in SAPO-34 manufacture they are not as effective as CHA or LEV structure type zeolite seeds.

Example 11

In this example the effectiveness in catalysing the
methanol to olefin conversion of the products made and
discussed in Example 5 was measured. In a bench scale fixed
bed reactor maintained at 450°C methanol diluted with
nitrogen (total pressure-atmospheric, partial pressure of
methanol 0.12) was passed over a catalyst at WHSV (based on
methanol) of 1 hr⁻¹ and a GHSV (based on methanol plus
nitrogen) of about 5500 hr⁻¹. After 1 hour on stream at 100 %
methanol conversion, the results were as shown in the Table.

20	Yield, %	Example 5 Seeded	Example 5 Unseeded
	C ₂ =	50.1	47.9
	C ₃ =	28.0	33.4
25	$C_2 = + C_3 = + C_4 =$	85.6	91.4
	C ₁ to C ₄ sats.	11.0	6.1

The yield of the more desirable ethylene is increased by about 5% using the product obtained with seeding compared 30 with the unseeded product.

molecular sieve.

1.0

15

CLAIMS

 A process for the manufacture of a crystalline molecular sieve containing phosphorus in its framework, which process
 comprises treating a synthesis mixture comprising elements necessary to form the phosphorus-containing molecular sieve and colloidal crystalline molecular sieve seeds for a time and at a temperature appropriate to form the desired

 A process as claimed in claim 1, wherein the phosphoruscontaining molecular sieve is an aluminophosphate or a silica-aluminophosphate, optionally containing other elements.

- 3. A process as claimed in claim 1 or claim 2, wherein the phosphorus-containing molecular sieve is of the CHA or LEV structure type.
- 20 4. A process as claimed in claim 1 or claim 2, wherein the phosphorus-containing molecular sieve is SAPO-34.
- 5. A process as claimed in claim 4, wherein the percentage area contribution of Broensted acid sites to the total OH 25 area in the IR spectrum is at least 30%.
 - 6. A process as claimed in claim 5, wherein the said contribution is at least 50%.
- 30 7. A process as claimed in any one of claims 4 to 6, wherein the SAPO-34 is Ni-SAPO-34.
 - A process as claimed in any one of claims 1 to 7, wherein the seeds are of structure type LEV, OFF, or CHA.

 A process as claimed in any one of claims 1 to 7, wherein the seeds are of Levyne, ZSM-45, Chabasite, Offretite, or SAPO-34.

5

10. A process as claimed in any one of claims 1 to 9, wherein the seeds are present in a proportion within the range of 1 to 2000 ppm, based on the total weight of the synthesis mixture.

10

- 11. A process as claimed in claim 10, wherein the proportion is within the range of from 100 to 1500 ppm.
- 12. A process as claimed in claim 10, wherein the proportion $15\,$ is within the range of from 100 to $250\,$ ppm.
 - 13. A process as claimed in any one of claims 1 to 12, wherein the seeds are incorporated in the synthesis mixture in the form of a suspension.

20

- 14. A process as claimed in any one of claims 1 to 13, wherein the particle size of the seeds is within the range of from 5 to 1000 nm.
- $25\,$ 15. A process as claimed in claim 14, wherein the particle size is within the range of from 10 to 300 nm.
 - 16. A process as claimed in claim 14, wherein the particle size is within the range of from 20 to 100 nm.

30


17. A process as claimed in any one of claims 1 to 16, wherein the phosphorus-containing molecular sieve is of a first structure type and the seeds are of a second structure type.

15

20

25

- 18. A process as claimed in claim 17, wherein the first structure type is CHA and the second structure type is LEV.
- 5 19. A molecular sieve whenever produced by a process as claimed in any one of claims 1 to 18.
- 20. SAPO-34 in which the percentage area contribution of Broensted acid sites to the total OH area in the IR spectrum 10 is at least 30%, obtainable by a process as claimed in any one of claims 1 to 18.
 - 21. A molecular sieve as claimed in claim 19 or claim 20, in particulate or layer form.
 - 22. A process for the conversion of an oxygenate to olefins which comprises contacting the oxygenate under catalytic conversion conditions with a molecular sieve as defined in any one of claims 19 to 21.
 - 23. The use of the molecular sieve as claimed in any one of claims 19 to 21, if desired after washing, cation exchange, or calcining, in hydrocarbon conversion, adsorption, or separation.
 - 24. The use, in the synthesis of a phosphorus-containing crystalline molecular sieve of colloidal crystalline molecular sieve seed crystals to control the particle size of the product, or to accelerate the formation of the product, or both to control the particle size and accelerate the
- 30 or both to control the particle size and accelerate the formation of the product.



SUBSTITUTE SHEET (RULE 26)

Case Docket	98M035
No.	

"PATENT"

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, mailing address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

names are fisted below)		anufacture of Molecular Si	it is sought on the invention entitled
the specification of wh	ich is attached hereto unless th	e following box is checked:	
[X] was filed on _	July 28, 1999 as Interr	ational Application No.	PCT/GB99/02480
	ve reviewed and understand to ment specifically referred to ab		ntified specification, including the claims, as
continuation-in-part app		which became available betw	ty as dfined in 37 CFR 1.56, including for even the filing date of the prior application and
miventor's certificate, or States of America, list	365(a) of any PCT internation ed below and have also ident	nal application which designatified below, by checking the	 of any foreign application(s) for patent of ted at least one country other than the United e box, any foreign application for patent or e that of the application on which priority is
] Prior Foreign Application	on Number(s)	Foreign Filing Date	Priority Not Claimed
GB 9816505.3	Great Britain	July 29, 1998	[]
(Number)	(Country)	(Month/Day/Year File	
GB 9816508.7	Great Britain	July 29, 1998	[]
(Number)	(Country)	(Month/Day/Year File	
L hereby claim the bene (Application N		(2) of any United States prov (Filing Date)	risional application(s) listed below.
(Application N	(umber)	(Filing Date)	
application designating not disclosed in the pr U.S.C. § 112, I acknow	the United States, listed below or United States or PCT Inte- ledge the duty to disclose mat	and, insofar as the subject ma mational application in the re erial information which is ma	ion(s), or § 365(c) of any PCT International atter of each of the claims of this application is nanner provided by the first paragraph of 35 sterial to patentability as defined in 37 CFR § ne national or PCT International filing date of
(Application Serial No.)	(Filing I	ate) (S	tatus - patented, pending, abandoned)
(Application Serial No.)	— (Filing I	ate) (S	tatus - patented, pending, abandoned)

Case Docket	98M035
No.	

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

NAMES	REGISTRATION NUMBERS	
C. Milton Fick	33,383	
James A. Zboray	35,420	
Edward F. Sherer	29,588	
Andrew B. Griffis	36,336	
Lou N. Moreno	44,953	
Dennis P. Santini	26,029	
Paul T. LaVoie	36,861	

Thereby declare that all statements made herein of my own knowledge are true and that all statements made on information and splid are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF	LAST NAME	FIRST NAME		MIDDLE NA	ME
INVENTOR	Verduijn	Johannes		Petrus	
FULL NAME OF	LAST NAME	FIRST NAME		MIDDLE NA	ME
OF EXECUTRIX	van den Berge	Jannetje		Maatje	
RESIDENCE &	CITY	STATE OR FOREIGN O	COUNTRY	COUNTRY C	F CITIZENSHIP
CITIZENSHIP	3233 BB Oostvoorne	The Netherlands The Nether		The Netherlan	ds
₱OST OFFICE	POST OFFICE ADDRESS	CITY	STATE OR	COUNTRY	ZIP CODE
ADDRESS	Fazantenlaan 26	3233 BB Oostvoorne	The Netherl	ands	

C Signature

ADDRESS

On behalf of Johannes Petrus Verduijn, JANNETJE MAATJE VAN DEN BERGE, Executrix of the Estate of Johannes P. Verduijn Date

FULL NAME LAST NAME FIRST NAME MIDDLE NAME OF INVENTOR Mertens Maria Wilfried Machteld RESIDENCE & STATE OR FOREIGN COUNTRY COUNTRY OF CITIZENSHIP CITIZENSHIP Boortmeerbeek Belgium 3190 Belgium POST OFFICE POST OFFICE ADDRESS CITY STATE OR COUNTRY ZIP CODE

Boortmeerbeek

Inventor's signature

Beringstraat, 72

Belgium 3190

: July 3,

Case Docket	98M035
No.	

2. -05

FULL NAME LAST NA				
	ME FIRST NAM	E	MIDDLE	NAME
OF INVENTOR Mortier	Wilfried		Jozef	
RESIDENCE & CITY	STATE OR I	FOREIGN,COUNTRY	COUNTR	Y OF CITIZENSHIP
CITIZENSHIP Kessel-Lo		ium	Belgium	
STREET STREET		STATE OR C	COUNTRY	ZIP CODE
ADDRESS Diestse-Ste	eenweg 483 Kessel-Lo	B-3010	Belgium	
Inventor's signature		Date	03/1	uly/2001
FULL NAME LAST NA	ME FIRST NAM	С	MIDDLE	NIA MET
OF INVENTOR Janssen	Marcel	L	Johannes	NAIVIE
RESIDENCE & CITY		OREIGN COUNTRY		Y OF CITIZENSHIP
CITIZENSHIP Kessel-Lo			Dutch	1 Of CHIZENSHIP
POST OFFICE ADDRESS		STATE OR		ZIP CODE
ADDRESS Domeinstr		B-3010 Belg		ZII CODE
9-00			/ /	
FULL NAME LAST NAME OF INVENTOR Van Oorse			MIDDLE	
RESIDENCE & CITY	chot Cornelius	corners	Wilhelmu	
	P 2020 P. le	OKERON GOOMIKI	COUNTR	y OF CITIZENSHIP
ETTIZENSHIP Brasschaa				Y OF CITIZENSHIP
POST OFFICE ADDRESS	CITY	STATE OR	COUNTRY	
POST OFFICE ADDRESS ADDRESS Ploegseba	CITY	STATE OR B-2930 Belg	COUNTRY	Y OF CITIZENSHIP ZIP CODE
POST OFFICE ADDRESS ADDRESS Ploegsebar Inventor's signature	San 136 CTTY Brasschaat whele W.M. van (i) or s	STATE OR B-2930 Belg	COUNTRY jum O3 Jul	Y OF CITIZENSHIP ZIP CODE
FULL NAME LAST NAI	San 136 CTTY Brasschaat renelis U.M. Van (i) or 1 ME FIRST NAM	STATE OR B-2930 Belg	COUNTRY jum O3 Jul	Y OF CITIZENSHIP ZIP CODE
FULL NAME OF INVENTOR Vaughan	ME FIRST NAM David	STATE OR B-2930 Belg	COUNTRY ium O3 Jul MIDDLE I E.W.	Y OF CITIZENSHIP ZIP CODE NAME
POST OFFICE ADDRESS ADDRESS Ploegsebar Inventor's signature Inve	E CTTY an 136 Brasschaat renelin W.M. van (i) or it ME FIRST NAM David STATE OR F	STATE OR B-2930 Belg Date E COREIGN COUNTRY	O3 Jul	Y OF CITIZENSHIP ZIP CODE
POST OFFICE ADDRESS ADDRESS Ploegsebat Inventor's signature Inventor's signature Inventor's signature Valent FULL NAME OF INVENTOR Vaughan GIVENTOR Vaughan CITY	ME FIRST NAM David STATE OR F Pensylvania	STATE OR B-2930 Belg Date E COREIGN COUNTRY	O3 Jule MIDDLE I E.W. COUNTRY	Y OF CITIZENSHIP ZIP CODE NAME

1/BPC\LAW\DOCUMENT\EF\$\2000 Documents\01cfs137 (98M035 Dec	1.).doi

Inventor's signature

Date _____

Case Docket	98M035
No.	

•••	PA	T	F.	M	Γ,

DECLARATION FOR PATENT APPLICATION

On behalf of Inventor JOHANNES PETRUS VERDUIJN, I, Jannetje Maatje Van Den Berge, hereby declare that I am a citizen of the Netherlands, reside at Fazantenlana 26, 3233 BB Oostvoorne, The Netherlands, and am the Executrix of the Estate of Johannes Petrus Verduijn, deceased, late a citizen of the Netherlands.

Upon information and belief, I believe that Johannes Petrus Verduijn is an original, first and joint inventor (plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"Processes for Manufacture of Molecular Sieves"

the specification of which is attached hereto unless the following box is checked:

[X]	was filed on	July 28, 1999	as International Applica	ation No.	PCT/GB99/02480	
			hat I have reviewed and endment referred to above		ntents of the above identified specifica	tion,
I acki	nowledge the du ode of Federal R	ty to disclose informat egulations, § 1.56.	ion which is material to	the examination of	of this application in accordance with	Title
inven	tor's certificate(s	s), or § 365(a) of any	PCT International applic	cation which desi	of any foreign application(s) for pate gnated at least one country other than	n the
Certif	d States, listed b icate(s), or PCT	elow and have also ide International application	ntified below, by checkir on having a filing date be	ng the box, any fo fore that of the ap	reign application(s) for patent or inver plication on which priority is claimed.	ıtor's
Prior	Foreign Applica	tion Number(s)	Foreig	n Filing Date	Priority Not Claimed	
GB 9	816505.3 (Number)	Great Britain (Cou		29, 1998 th/Day/Year Filed)	[]	
GB 9	816508.7 (Number)	Great Britain (Cou		29, 1998 th/Day/Year Filed)	[]	
Ehere kik	by claim the ben			ted States provision	onal application(s) listed below.	
	(Application	Number)	•	(Filing Date)		
applic not di U.S.C 1.56 v	cation designating isclosed in the p 2. § 112, I ackno	g the United States, list prior United States or wledge the duty to dis	ed below and, insofar as PCT International applic close material information	the subject matte cation in the man on which is mater	(s), or § 365(c) of any PCT Internat of each of the claims of this application ner provided by the first paragraph of all to patentability as defined in 37 CI tational or PCT International filling da	on is of 35 FR §
(Ap	plication Serial No.)		(Filing Date)	(Status	- patented, pending, abandoned)	
(Арј	plication Serial No.)		(Filing Date)	(Status	- patented, pending, abandoned)	

Case Docket	98M035
No.	

		and/or agent(s) to prosecute this

	NAMES REGISTRATION NUMBERS					
	C. Milton Fick	33,383				
	James A. Zboray	35,420				
	Edward F. Sherer	29,588				
ì	Andrew B. Griffis	36,336				
1	Lou N. Moreno	44,953				
	Dennis P. Santini	26,029				
	Paul T. LaVoie	36,861				

SEND CORRESPONDENCE TO:	DIRECT TELEPHONE CALLS TO:	
	(Name and Telephone Number)	
Exxon Chemical Company		
Law Technology	Edward F. Sherer	1
P.O. Box 2149	(281) 834-5933	1
Baytown, Texas 77522-2149	Facsimile No. (281) 834-2911	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so finade are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

4	FULL NAME OF	LAST NAME	FIRST NAME		MIDDLE NA	ME
	INVENTOR	Verduijn	Johannes		Petrus	
	FULL NAME OF	LASTNAME	FIRST NAME		MIDDLE NA	ME
	OF EXECUTRIX	van den Berge	Jannetje		Maatje	
- 1	RESIDENCE &	CITY	STATE OR FOREIGN C	OUNTRY	COUNTRY O	F CITIZENSHIP
- 1	CITIZENSHIP	3233 BB Oostvoorne	The Netherlands		The Netherlan	ds
- (POST OFFICE	POST OFFICE ADDRESS	CITY	STATE OR	COUNTRY	ZIP CODE
1	ADDRESS	Fazantenlaan 26	3233 BB Oostvoorne	The Netherl	ands	

Signature ___

On behalf of Johannes Petrus Verduijn, JANNETJE MAATJE VAN DEN BERGE, Executrix of the Estate of Johannes P. Verduijn Date July 4 2001

FULL NAME	LAST NAME	FIRST NAME		MIDDLE NAME
OF INVENTOR	Mertens	Machteld		Maria Wilfried
RESIDENCE &	CITY	STATE OR FOREIG	N COUNTRY	COUNTRY OF CITIZENSHIP
CITIZENSHIP	Boortmeerbeek	Belgium 3190		Belgium
POST OFFICE	POST OFFICE ADDRESS	CITY	STATE OR CO	UNTRY ZIP CODE
ADDRESS	Beringstraat, 72	Boortmeerbeek	Belgium 3	190

Inventor's signature	Date	

Case Docket	98M035
No	

Date

FULL NAME	LAST NAME	FIRST NAME		MIDDLE	NAME
OF INVENTOR	Mortier	Wilfried		Jozef	
RESIDENCE &	CITY	STATE OR FORE	IGN COUNTRY	COUNT	RY OF CITIZENSHIP
CITIZENSHIP	Kessel-Lo	B-3010 Belgium		Belgium	
STREET	STREET ADDRESS	CITY	STATE OR CO	UNTRY	ZIP CODE
ADDRESS	Diestse Steenweg 483	Kessel-Lo	B-3010 Be	lgium	-

FULL NAME LAST NAME FIRST NAME MIDDLE NAME OF INVENTOR Janssen Marcel Johannes STATE OR FOREIGN COUNTRY RESIDENCE & CITY COUNTRY OF CITIZENSHIP CITIZENSHIP B-3010 Belgium Kessel-Lo Dutch POST OFFICE ADDRESS CITY STATE OR COUNTRY ZIP CODE ADDRESS Domeinstraat 84 Kessel-Lo B-3010 Belgium

Inventor's signature			Date		
FULL NAME	LAST NAME	FIRST NAME		MIDDLE NAME	
OF INVENTOR	Van Oorschot	Cornelius		Wilhelmu	s, Maria
RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY		COUNTRY OF CITIZENSHIP	
CITIZENSHIP	Brasschaat	B-2930 Belgium		Dutch	
POST OFFICE	ADDRESS	CITY	STATE OR CO	UNTRY	ZIP CODE
ADDRESS	Ploegsebaan 136	Brasschaat	B-2930 Belgiui	n	

Inventor's signature ______ Date _____

FULL NAME	LAST NAME	FIRST NAME		MIDDLE	NAME
OF INVENTOR	Vaughan	David		E.W.	
RESIDENCE &	CITY	STATE OR FOREIG	IN COUNTRY	COUNTR	Y OF CITIZENSHIP
CITIZENSHIP	State College	Pennsylvania		USA	
POST OFFICE	ADDRESS	CITY	STATE OR CO	UNTRY	ZIP CODE
ADDRESS	528 Hillcrest Avenue	State College	PA		16803

Inventor's signature	Date	

INBPOLLAW/DOCUMENT/EFS/2000 DOCUMENTS/01EFS/137 (98M035 DECL. VERDUIJN'S WIFE), DOC

Inventor's signature

United States Patent & Trademark Office Office of Initial Patent Examination - Scanning Division



Application deficiencies f	ound during	scanning:	
Page(s) 4 of 4 for scanning.	of the	declaration	_ were not present
for scanning	•	(Document title)	
□ Page(s)for scanning.	_of	(Document title)	were not present

Scanned copy is best available.